

INFORMATION SHEET

Disinfecting tunnel Clean Tunnel



INTENDED USE:

CLEAN TUNNEL is designed to disinfect people in facilities where mass events are organized. Stainless steel passage construction ensures full safety of use. The use of proven components and modern solutions guarantees reliable operation. The control system allows you to program the decontamination time and the amount of disinfectant solution used. The tunnel provides easy access for people in wheelchairs.

HOW TO USE:

When the tunnel is started, a system of nozzles is activated, which applies the disinfectant solution to people passing through the tunnel. Micro drops of disinfectant solution penetrate the pores of clothes and settle on their surface destroying viruses, bacteria and fungi. The amount of solution applied does not cause soaking and destroying the clothes. During disinfectant application, the cabin lights up red.

Technical parameters

Disinfection tunnel CLEAN TUNNEL



Application	Contactless body disinfection
External dimensions	1200 x 2500 x 2300 mm (W x D x H)
Passage dimensions	1000 x 2450 x 2050 mm (W x D x H)
Housing material	Stainless steel
Operating temperature	-10 deg. +50 deg. Celsius
Weight	465 kg
Power supply	230V/50Hz
Disinfection method	Misting with disinfectant
Disinfecting agent	Disinfectant used to destroy viruses, bacteria and fungi, sprayable. Complete approvals and certifications.
Capacity	ca. 2000 persons/hour.
Spray time	3– 5 seconds
Tank volume:	50 litres
Tank fluid level	Light signals
Tank material	Acidproof steel
Number of spray nozzles	14
Silhouette detection	Photocell
Operating mode	Automatic
Country of origin	Poland
Warranty	12 months